

For Earth, For Life
Kubota

Z

KUBOTA ZD-SERIES

ZD1211



Makes work a pleasure

Kubota developed the ZD-Series zero-turn mowers for professionals who need to achieve top results every day. Extreme manoeuvrability, ease of operation and maintenance and – last but not least – the impressive large-area performance of these mowers make your work easier.

Powerful Kubota diesel engines

The modern diesel engines offer unparalleled power, productivity and fuel economy, even during demanding mowing jobs.

New low-profile tyres

The low-profile tyres on the rear axle further improve the stability and traction of the ZD-Series on lawns. Thanks to their large tread area, they also protect the lawn from damage during mowing.

Transmission with shaft drive

Kubota's large-volume, shaft-driven hydrostatic transmission features a smooth, quiet and maintenance-free axle drive. Power is transmitted via a shaft directly from the engine to the transmission and from there to the tyres via a toothed gear.

Long operating times

The 49L fuel tank enable long periods of mowing without refuelling.

User-friendly and comfortable

The comfortable operator's platform is equipped with a large driver's seat. All control functions are easily accessible and simple to operate.

Hydraulic mower deck lift

The hydraulic mower deck lift is operated with two pedals. Because you can raise and lower the mower unit with your foot, you can easily continue mowing regardless of obstacles.

Optional mulching equipment

With a 152 cm rear discharge, the ZD-Series mowers are also available with optional mulching equipment.

Outstanding driving stability

The low centre of gravity allows you to work safely. Together with the large rear wheels, long wheelbase and fuel tanks positioned above the tyres and under the seat, the ZD-Series provides excellent driving stability.

#Features



Large and bright new LCD display

The generous LCD display – the largest in its class – presents all the essential information you need to maximise cutting performance, including oil pressure, water temperature, fuel level and voltage. The hour meter keeps you informed of upcoming maintenance and service intervals.



New ergonomically arranged controls

For faster operation and better ergonomics, all the mower's controls are within reach of your right hand, allowing you to quickly and easily adjust the cutting height. It is also very easy to see the cutting height setting, which further simplifies adjustment work.



Tilt-up system for easy maintenance

With Kubota's innovative two-bolt tilt-up system, routine maintenance under the mower is quick and easy. All you need to do is lift the front of the mower, to have an easy access to the blades.



Mower unit with rear discharge

The rear discharge system generates a uniform airflow, which ensures that all the cut material is ejected homogeneously. It can be fitted with an optional mulching kit.

New mulching equipment (option)

Kubota has redesigned the mulching equipment to produce even finer cuttings that are evenly distributed across the lawn. The result is a clean lawn that saves you time as well. The mulching equipment can be attached to both rear and side discharge mowers.

#Technical data

Model		ZD1211
Engine		
Type		Liquid-cooled, 3-cylinders diesel
Model		Kubota D1105
Engine gross power @ 3000 rpm (SAE 1995)	hp (kW)	25 (18,5)
Displacement	cm ³	1,123
Air cleaner indicator		Standard
Fuel tank capacity	l	49
Transmission		
2 HST with integrated transaxle		
Tyre size		
Front		15 x 6.5 – 8, smooth semi-pneumatic
Rear		26 x 12.0 –16 turf, low profile tyre
Travelling speed range		
Forward	km/h	0 – 17.0
Reverse	km/h	0 – 8.5
Dimensions		
Overall length	mm	2,260
Overall width	with mower	1,875 (side)/1,600 (rear)
Overall height	Rops upright	2,000
	Rops folded	1,640
Wheelbase	m	1,440
Tread	Front	1,064
	Rear	1,210
Weight with mower (w/o fuel)	kg	790
Mower deck		
Discharge direction		Side/rear/mulching (available as option for both side and rear)
Mower deck construction		Fabricated
Deck depth	mm	140
Deck steel thickness	mm	4.2
Mower lift system		Hydraulic lift by foot pedal
Mower deck drive system		Shaft Drive
Anti-scalp roller		Caster x 2, rigid x 4
Cutting width	cm (inch)	152 (60)
Cutting height adjustment		Dial
Cutting height range	mm	25-127
Cutting height increments	inch	0.25
Number of blades		3
Front axle		
Selective ‚Fix‘ and ‚Oscillating‘ front axle		
Maintenance lift system		
Standard		
Display		
LCD panel (hour meter, fuel gauge, coolant temperature gage, battery voltage met)		
Seat		
High back deluxe seat with reclining and lumbar support		
Seat suspension stroke	mm	76
Step open system for easy maintenance		
Standard		
Rops		
Foldable		

The company reserves the right to change the above specifications without notice.
 This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional, and not standard equipment.
 Please contact your local Kubota dealer for warranty, safety or product information.

Kubota (U.K.) Limited

Dormer Road Thame, Oxfordshire, OX9 3UN

<http://www.kubota.co.uk>

This publication may not be reproduced in whole or in part in any form without the prior written consent of KUBOTA. It corresponds to the status at the time of going to press. The manufacturer reserves the right to change technical specifications without notice. Some of the parts shown in the publication are optional and are not part of the standard equipment. Information on warranty and safety as well as further product information can be obtained from the responsible KUBOTA authorized dealer.

v_1/2021

